

Belt-Drive Power Blower



Proven Performance. Unmatched Durability.

- Front and rear safety grills feature a continuous spun wire with eight tie points, meeting strict European CE Safety Standards.
- *Winning Step* is the only patented foot-operated tilt mechanism offered today, featuring four back and one forward tilt positions. Ideal for basements, cellars and other PPV applications, the *Winning Step* is an exclusive Tempest feature.
- The Turbo 2000 Shroud increases air velocity by up to 30%. Air hitting the ventilation opening is stronger and maintains the *cone of air* farther downwind.
- Heavy Duty 9" Pneumatic tires are standard on all units (except 16"). Designed to handle a variety of terrain types, these tires make transport a snap with no brakes to lock or unlock.
- The exclusive flip-up handle makes transporting to and from a ventilation site easy. Handle quickly flips up to automatically lock firmly in position. Releases with two fingers and one hand to fold away for storage.

Only Tempest Belt-Drive Gasoline Powered Blowers provide these outstanding standard features:

Using a Tempest Belt-Drive engine allows the motor to be placed lower on the chassis creating less air blockage to the intake side of the blower.

Airflow from the face of the blower is smoother and more controllable, allowing for more effective PPV and PPA with more down stream air pressure!

The position of the engine also lowers the blower's center of gravity. This helps provide extra stability while the blower is running at higher speeds. It also makes the unit more balanced, making transport faster and safer.

The belt on the engine absorbs the inherent motor vibrations as well as any air intake distortion. Stress directly on the engine shaft is eliminated by the jackshaft that turns the impeller, extending the life of the engine and your power blower.



21" Belt-Drive Blower

Model	Part #	Size	Engine, HP	CFM	RPM	Width	Depth	Height	Lbs.
BD18-H-5.5	700-103	18"	HON, 5.5	15,023	3,870	21.50	21.00	24.25	85
BD21-H-6.5	700-021	21"	HON, 6.5	17,743	3,125	25.00	22.00	26.25	93
BD24-H-6.5	700-020	24"	HON, 6.5	18,130	3,175	28.25	22.00	31.00	92
BD27-H-9.0	700-268	27"	HON, 9.0	23,943	2,672	30.50	23.50	32.50	155

HON = Honda / Lbs = Dry Weight

Distributed Exclusively by:

Tempest Technology Corp.

4708 N. Blythe Ave. • Fresno, CA 93722 • 800.346.2143 • t: 559.277.7577 • f: 559.277.7579
www.tempest-edge.com • response@tempest-edge.com